

# AF ARCADE FR

## Technical sheet

Recommended use : Small structures, Terrace awnings, Awnings, Sail shade



Characteristics	Values		Units	Standards
	Warp	Weft		
<b>General characteristics</b>				
Base cloth	550 dTex PES HT 495 den			
Coating	PVC coating both side			
Finish	Cleangard lacquer both sides			
Weight	500		g/m <sup>2</sup>	ISO 3801
Width	150 150 250 250 302 302		cm	
Roll length	30 60 30 60 30 60		ml	

## Fabric resistance

Tensile strength	150	150	daN/5cm	NF EN ISO 1421
Tear strength	15	15	daN	DIN 53.363
Adhesion	7		daN/5cm	NF EN ISO 2411
Elongation under load	<1	<3	%	NF EN 15619
Residual deformation	<0.4	<1.2	%	NF EN 15619
Cold resistance	-30		°C	NF EN 1876-2
Warm resistance	70		°C	[24h]
Fire resistance	M2			NF P 92 503
	B1			DIN 4102
	BS			BS 7837
	B-s2-d0			Euroclasses EN 13501-1
	NFPA 701			NFPA 701
	CSFM Title19			CSFM Title 19



## AnsonFabrics Co.

No.36 Fenghuang Road  
Qianjiang Industry Zone  
Haining, 314413  
82.5730.5258  
(customer service)  
86.182.5832.6285  
INFO@ANSONFABRICS.COM

