

DS 720 TEX

Technical sheet

Recommended use : Textile architecture

Comments : This is not a standart product, only on request

Characteristics	Values		Units	Standards
	Warp	Weft		
General characteristics				
Base cloth	1100 dTex PES HT 990 den			
Coating	PVC coating both side			
Finish	PVDF lacquer both sides			
Weight		720	g/m ²	ISO 3801
Width	300	300	cm	
Roll length	60	250	ml	
Fabric resistance				
Tensile strength	260	250	daN/5cm	NF EN ISO 1421
Tear strength	32	28	daN	DIN 53.363
Adhesion		10	daN/5cm	NF EN ISO 2411
Elongation under load	<1	<2	%	NF EN 15619
Residual deformation	<0.4	<0.8	%	NF EN 15619
Cold resistance		-40	°C	NF EN 1876-1
Warm resistance		70	°C	[24h]
Fire resistance		M2		NF P 92 503
		B1		DIN 4102
		BS		BS 7837
		B-s2-d0		Euroclasses EN 13501-1
		NFPA 701		NFPA 701



AnsonFabrics Co.

No.36 Fenghuang Road
Qianjiang Industry Zone
Haining, 314413

82.5730.5258
(customer service)

86.182.5832.6285

INFO@ANSONFABRICS.COM

