

AF 900 FT

Technical sheet

Recommended use : Flexible Tank, Retention pond

Comments : This product is not in accordance with the requirements of the European regulations UE-n°10/2011

Characteristics	Values			Units	Standards
	Warp		Weft		
General characteristics					
Base cloth	1100 dTex PES HT				
	990 den				
Coating	PVC coating both side				
Finish	Cleangard lacquer both sides				
Weight	900			g/m ²	ISO 3801
Width	300	300	300	cm	
Roll length	30	60	200	ml	

Fabric resistance

Tensile strength	400	400	400	daN/5cm	NF EN ISO 1421
Tear strength	60	50	50	daN	DIN 53.363
Adhesion	10			daN/5cm	NF EN ISO 2411
Puncture resistance	8			kN	NF EN 12236
Cold resistance	-30			°C	NF EN 1876-2
Warm resistance	70			°C	{24h}
Overall migration (MG2 - Water)	< 10			mg/dm ²	NF EN 1186-1 & 3
Fire resistance	< 100			mm/min	DIN 75 200



AnsonFabrics Co.

No.36 Fenghuang Road
Qianjiang Industry Zone
Haining, 314413
82.5730.5258
(customer service)
86.182.5832.6285
INFO@ANSONFABRICS.COM

