

AF 900 JET

Technical sheet

Recommended use : Printed truck curtains, Truck side curtains

Comments : Bicolor - Endroit blanc (7325) / Envers gris (939)

Range : Truck

Printing : digital inkjet printing

Printable side : Outside

Ink : Solvent, UV, Latex Ink

Characteristics	Values		Units	Standards
	Warp	Weft		
General characteristics				
Thickness	0.72		mm	ISO 5084
Base cloth	1100 dTex PES HT 990 den			
Coating	PVC coating both side			
Finish	Inkjet lacquer one side - Grey back			
Weight	900		g/m ²	ISO 3801
Translucency	0		%	XPT 54199
Width	300	300	cm	
Roll length	35	50	m	

Fabric resistance

Tensile strength	400	400	daN/5cm	NF EN ISO 1421
Tear strength	60	50	daN	DIN 53.363
Adhesion	10		daN/5cm	NF EN ISO 2411
Cold resistance	-30		°C	NF EN 1876-2
Warm resistance	70		°C	(24h)
Fire resistance	< 100		mm/min	DIN 75 200



AnsonFabrics Co.

No.36 Fenghuang Road
Qianjiang Industry Zone
Haining, 314413
82.5730.5258
(customer service)
86.182.5832.6285
INFO@ANSONFABRICS.COM

