

# AF DO 680

## Technical sheet

Recommended use : Flexible doors, Tarpaulins for agriculture, Covers and lagging, Truck Tarpaulins, Truck roofing

Characteristics	Values		Units	Standards
	Warp	Weft		
<b>General characteristics</b>				
Base cloth	1100 dTex PES HT			
	990 den			
Coating	PVC coating both side			
Finish	Cleangard lacquer both sides			
Weight	680		g/m <sup>2</sup>	ISO 3801
Width	150 250 250 250 300 300	300	cm	
Roll length	60 30 60 250 30 60	250	m	
<b>Fabric resistance</b>				
Tensile strength	260	250	daN/5cm	NF EN ISO 1421
Tear strength	32	28	daN	DIN 53.363
Adhesion	10		daN/5cm	NF EN ISO 2411
Cold resistance	-30		°C	NF EN 1876-2
Warm resistance	70		°C	(24h)
	< 100		mm/min	DIN 75 200
	< 100		mm/min	ISO 3795 : 1989



## AnsonFabrics Co.

No.36 Fenghuang Road  
 Qianjiang Industry Zone  
 Haining, 314413  
 82.5730.5258  
 (customer service)  
 86.182.5832.6285  
 INFO@ANSONFABRICS.COM

