

AF STREAK670

Technical sheet

Recommended use : Awnings, Small structures, Terrace cover

| Characteristics | Values | | Units | Standards |
|--------------------------------|------------------|------|------------------|------------------------|
| | Warp | Weft | | |
| General characteristics | | | | |
| Coating | PVC | | | |
| Base cloth | 1100 dTex PES HT | | | |
| | 990 den | | | |
| Weight | 670 | | g/m ² | ISO 3801 |
| Width | 218 | | cm | |
| Roll length | 65 | | ml | |
| Fabric resistance | | | | |
| Tensile strength | 250 | 250 | daN/5cm | NF EN ISO 1421 |
| Tear strength | 27 | 27 | daN | DIN 53.363 |
| Adhesion | 10 | | daN/5cm | NF EN ISO 2411 |
| Cold resistance | -40 | | °C | NF EN 1876-1 |
| Warm resistance | 70 | | °C | (24h) |
| Fire resistance | M2 | | | NF P 92 503 |
| | BS | | | BS 7837 |
| | B-s2-d0 | | | Euroclasses EN 13501-1 |



AnsonFabrics Co.

No.36 Fenghuang Road
Qianjiang Industry Zone

Haining, 314413

82.5730.5258

(customer service)

86.182.5832.6285

INFO@ANSONFABRICS.COM

